

Cinelex SKYNODE-TX

Plug & Play Wireless DMX Transmitter

GO WIRELESS

Add wireless functionality to any DMX control desk, giving a new lease of life to existing equipment.

PLUG & PLAY

Simply insert SKYNODE-TX to the controller's DMX output XLR connector to get started.

SIMPLE SYNCHRONISATION

Link to any LumenRadio receiver with a single button-press.

SMALL, YET MIGHTY

Compact design ensures clean integration with any DMX controller.

USB-POWERED

Power SKYNODE-TX from any 5V USB source.



Wireless Protocol

| | |
|-----------------------|------------------------------------|
| Protocol | LumenRadio |
| Operational Frequency | 2.4GHz (2402-2480MHz) |
| Range | Up to 100m (environment dependent) |
| DMX Standards | DMX512, DMX512 (1990) & DMX512-A |

Power

| | |
|-------------------|----|
| Micro-USB | 5V |
| Power Consumption | 1W |

Controls

| | |
|------------------|--------------------------------------|
| 1x "SYNC" Button | Synchronise SKYNODE-TX with Receiver |
|------------------|--------------------------------------|

Connectors

| | |
|---------------------------------|--|
| 1x DMX XLR 5-Pin Female | |
| 1x Micro-USB Power Input Female | |
| 1x Built-In Antennae | |

LED Indicators

| | |
|-----------------|--------------------------|
| 1x "STATUS" LED | Connection Status |
| 1x "POW" LED | Power Input Confirmation |

Size (with Antennae)

| | |
|------------|--------------------------------|
| Weight | 53g |
| Dimensions | 80mm x 26mm x 38mm (L x W x D) |